



Nora Shower Box

Product Disclosure Information Self-Assessment

Version: V1

Product Name	Nora Shower Box
Product Line	Nora Shower Box
Product Identifier	SG-MO-SD-9C1900, SG-MO-SD-1C1900, SG-MO-SD-12C1900, SG-MO-PD-9S1900, SG-MO-PD-D900, SG-MO-FP-900S, SG-MO-PD-1S1900, SG-MO-PD-D1000, SG-MO-FP-1000S, SG-MO-SD-12S1900, SG-MO-SD-D1200, SG-MO-CS-9S1900, SG-MO-CS-1S1900, SG-GR-PD-9D1900, SG-PD10D1900 STC9M, STC9C, STC1M, STC1C, STC12ML, STC12MR, STC12CL, STC12CR, STS12ML, STS12MR, STS12CL, STS12CR, STS999M, STS999CL, STS9M, STS9C, STS1M, STS1C, STS111M, STS111CL, STS12M3, STS12C3L, STD9M, STD9C, STD1M, STD1C SL9T, SL1T, SL1290T, SL999T, SL111T, SL9129T.

Product description

A complete Shower Box comprising an Acrylic Shower Tray, Easy-Clean Trap or Hi-Flow Waste, optional Shower Liner & a Pivot, Hinged or Sliding Shower Door (& Return, as applicable), intended for personal showering in residential & commercial buildings.

The shower tray is made from fibreglass & particle board reinforced Sanitary Grade Acrylic & features a 40mm high continuous up-stand on each side to be installed against a wall. Sanitary Grade Acrylic features a high gloss surface for ease of cleaning.

The shower Liner is made from a single, folded piece of 2.0mm (Acrylic) capped ABS sheet featuring an antimicrobial surface for hygiene & ease of cleaning.

The shower door (& return, as applicable) comprises Grade A toughened safety glass complying with AS/NZS 2208 & NZS 4223.3, with anodised aluminium framing & PVC seals. The hardware is in Stainless Steel, finished Zinc alloy & ABS. The silicone sealant for sealing the shower wall is white or translucent NG.

Square / Rectangular sizes: 900x900, 1000x1000, 1200x900 (LH or RH), 1200x1000 (LH or RH).

Round sizes: 900x900, 1000x1000, 1200x900 (LH or RH).

Alcove sizes: 750x900, 900x750, 900x900, 1000x1000, 1200x900

All sizes are nominal & specific availability varies according to the chosen range (identifier).

Relevant Building Code Clauses

B2 Durability — B2.3.1 (c)

E3 Internal moisture — E3.3.4, E3.3.5, E3.3.6

F2 Hazardous building materials — F2.3.1, F2.3.3

G1 Personal Hygiene — G1.3.2

Contributions to Compliance

B2.3.1(c): Per B2/AS1, Durability Requirements of Nominated Building Elements for Plumbing Fixtures, Nora Shower Box have a durability of at least 5 years, when installed and maintained in accordance with our supplied instructions. Nora Acrylic Shower Trays are designed & manufactured to AS 3588: 1996 (Shower bases and shower modules).

E3/AS1 3.3.1: Nora Acrylic Shower Tray & Shower Liner surfaces are impervious.

E3/AS1 3.3.1.1: The Nora Acrylic Shower Trays are made from fibreglass & particle board reinforced Sanitary Grade Acrylic.

E3/AS1 3.3.1.2: The Nora shower wLiners are made from a single, folded piece of 2.0mm Senosan® 3000X PMMA (Acrylic) capped ABS sheet, without any joints.

E3/AS1 3.3.2: The Nora Acrylic Shower Trays are constructed with 40mm high continuous moulded up-stand on each side to be installed against a wall.

E3/AS1 3.3.2.1: The minimum height for Nora / Renoarts shower doors & shower liner is 1900mm.

E3/AS1 3.3.2.2: The junction between the Nora Acrylic Shower Tray & Shower Liner is constructed in accordance with Figure 4 (b).

F2.3.1: No materials used in the construction of Nora Shower Box give rise to harmful concentrations at the surface of the material where the material is exposed, or in the atmosphere of any space.

F2.3.3: Per F2/AS1 1.1.1 All Glazing in Nora / Renoarts Shower Doors complies with NZS 4223: Part 3. Each glass panel is manufactured & marked in accordance with AS/NZS 2208. Please contact us for the current AS/NZS 2208:1996

G1.3.2: The Sanitary Grade Acrylic used in Nora Acrylic Shower Trays features a high gloss surface for ease of cleaning. The shower Liners also features a high gloss surface, in addition to an Antibac® antimicrobial surface for hygiene & ease of cleaning.

G1/AS1 2.6.1: Nora Acrylic Shower Trays are designed & constructed to AS 3588 (Shower bases and shower modules).

G12.3.5: Nora Shower Boxes must be provided with hot water to satisfy the intended usage of personal bathing (note – tapware not included).

G13/AS1 2.1.1: The Aquaknight Easy Clean Trap complies with AS 2887 & is Watermark certified to this standard under Licence no. WM-21417

G13/AS1 3.2.1: As a wastewater fixture trap, the Aquaknight Easy Clean Trap features a 75mm water seal.

Scope of Use

For interior installations in residential & commercial buildings with timber or concrete flooring.

Install as a complete Acrylic Shower Box (comprising Acrylic Shower Tray, Shower Liner & Shower Glass Set) or as a Tile Wall Option Shower Box (comprising Acrylic Shower Tray & Shower Glass Set only – Waterproofing & Tiles are not included).

Waste / drain holes are located either centrally or in the rear corner of the Nora Acrylic Shower Trays & must be fitted with the Aquaknight Easy Clean Trap or Hi Flow Waste which have standard DN40 waste outlets. Hot water must be supplied to

Conditions of Use

Nora Shower Box must be installed and maintained in accordance with our supplied instructions. Nora Acrylic Shower Trays must be fully supported and installed level. Shower Liners must be installed using only Shower-bond adhesive. The substrate must not have been previously plastered, sealed or painted. Gaps must be left in the adhesive pattern to allow solvent release. The edge of the wall liner should not be sealed until the adhesive has cured.

Sealing of the Shower Liner to the up-stand of the Nora Acrylic Shower Tray & the Nora / Renoarts Shower Door Set to the Nora Acrylic Shower Tray must be

completed only using Sikasil NG silicone sealant. Special attention must be paid to the specific requirement for each joint – please refer to the installation instructions for further information.

The tapware & waste must be installed by a Registered Plumber. The maximum permitted temperature of water at the shower outlet is 50 degrees Celsius.

Supporting documentation

The following additional documentation supports the above statements:

Installation instructions – Shower Tray Refer website.

Tray

Installation instructions – Easy Clean Trap Refer website.

Clean Trap

Installation instructions – Hi Flow Waste Refer website.

Waste

Installation instructions – Shower Wall Refer website.

Wall

Installation instructions – Shower Door Refer website.

Door

Warranty statement Refer website.

Care & maintenance guide Refer website.

Warnings and Bans

This product line is not subject to any warning or ban under section 26 of the Building Act 2004.

Contact details

Manufacture location	China
Legal and trading name of manufacturer and importer	Renoarts Ltd
Manufacturer/Importer Address for Service	25B Lorien Place, East Tāmaki, Auckland 2013
Manufacturer/Importer Website	www.renoarts.co.nz
Manufacturer/Importer NZBN	9429041423424
Manufacturer/Importer Email	info.n@renoarts.co.nz , info.e@renoart.co.nz
Manufacturer/Importer Phone Number	092716664