



Nora Shower Heads

Product Disclosure Information Self-Assessment

Version: V1

Product Name	Nora Shower Heads
Product Line	Nora Shower Heads
Product Identifier	100218-7

Product description

The Nora 100218-7 Shower Heads are manufactured to comply with AS/NZS 3662 standard. They are intended for use in residential & commercial applications, with equal mains pressure water supply system.

This model is rated at WELS 4 star, 7.5 litres/min.

This model is available in chrome finish.

Relevant Building Code Clauses

B2 Durability — B2.3.1 (c)

F2 Hazardous building materials — F2.3.1

G1 Personal Hygiene — G1.3.2

G12 Water Supplies — G12.3.2, G12.3.5

Contributions to Compliance

B2.3.1(c): Per B2/AS1, Durability Requirements of Nominated Building Elements for Plumbing Fixtures, The Nora Shower Heads have a durability of at least 15 years, when installed and maintained in accordance with our supplied instructions. The Nora Shower Heads are designed & manufactured to AS/NZS 3662 (Performance of showers for bathing) & are Watermark certified to this standard under Licence no. WM-26252.

F2.3.1: No materials used in the construction of Nora Shower Heads give rise to harmful concentrations at the surface of the material where the material is exposed, or in the atmosphere of any space.

G1.3.2: The Nora Shower Heads feature chrome or other durable finished surfaces for ease of cleaning.

G12/AS1 2.1.2: All Nora showering tapware are fit with 2 single check valves for back flow prevention.

Scope of Use

The Nora 100218–7 Shower Heads are intended for use with hot & cold water in residential & commercial applications, with equal mains pressure water supply systems.

They could be used on both slide shower configuration and dual rain shower configuration.

This models are supplied with GB 1/2” connection.

Conditions of Use

The Nora 100218–7 Shower Heads must be installed by a registered plumber in accordance with the supplied instructions & in compliance with the relevant requirements of AS/NZS 3500 & AS/NZS 6400.

The water supply pipes must be flushed thoroughly to remove any debris. In-line water filters must be used.

Recommended working pressure: 35kPa to 500kPa.

If pressure exceeds 500kPa, a pressure limiting valve must be installed.

The maximum permitted temperature of water at the outlet is 50 degrees Celsius.

This product is cleanable and impervious to moisture — cleaning shall be done in accordance with the supplied cleaning instructions.

Supporting documentation

The following additional documentation supports the above statements:

Installation instructions Refer website.

Warranty statement Refer website.

Care & maintenance guide Refer website.

Warnings and Bans

This product line is not subject to any warning or ban under section 26 of the Building Act 2004.

Contact details

Manufacture location	China
Legal and trading name of manufacturer and importer	Renoarts Ltd
Manufacturer/Importer Address for Service	25B Lorien Place, East Tāmaki, Auckland 2013
Manufacturer/Importer Website	www.renoarts.co.nz
Manufacturer/Importer NZBN	9429041423424
Manufacturer/Importer Email	info.n@renoarts.co.nz , info.e@renoart.co.nz
Manufacturer/Importer Phone Number	092716664