



Auckland East: 25B Lorien Place, East Tāmaki, Auckland 2013 092716664 info.e@renoarts.co.nz

Nora Back-to-Wall Toilets

Product Disclosure Information Self-Assessment Version: V1

| Product Name | Nora Back-to-wall Toilets |
|--------------------|--|
| Product Line | Nora Toilets |
| Product Identifier | TC-6672B TC-6672R TC-6601R K-800 RN-1001 |

Product description

Floor mounted back-to-wall toilets for installation in residential & commercial buildings.

Water conserving dual flush with WELS 4 star rating (3.3 litre average flush).

Pans & cisterns are made from white glazed vitreous china. Seats are made from highly durable UF (Urea Formaldehyde).

Supplied with a Watermark certified S trap pan connector to achieve a wide range of set outs (refer to specification sheet for each model). P trap installation with a straight pan connector.

TC-6672B, TC-6672R, TC-6601R, K-800 have top rear or side water inlet options.

RN-1001 have side water inlet only.

All toilets feature quick release seats for easier cleaning.

Relevant Building Code Clauses

B2 Durability - B2.3.1 (c)

F2 Hazardous building materials - F2.3.1

G1 Personal Hygiene - G1.3.2

G12 Water Supplies - G12.3.2

Contributions to Compliance

B2.3.1(c): Per B2/AS1, Durability Requirements of Nominated Building

Elements for Plumbing Fixtures, Nora Back-to-wall toilets have a durability of at least 5 years, when installed and maintained in accordance with our supplied instructions. Nora Back-to-wall toilets are designed & manufactured to AS 1172.1 (Sanitary plumbing products: Water closet pans) & AS 1172.2 (Sanitary plumbing products: Flushing devices and cistern inlet and outlet valves) & are Watermark certified to these standards under Licence no.WM-A030020. The vitreous china material used complies with AS 1776 (Vitreous china used in sanitary appliances). Supplied flexible hoses comply with AS/NZS 3499.



F2.3.1: No materials used in the construction of Nora Back-to-wall toilets give rise to harmful concentrations at the surface of the material where the material is exposed, or in the atmosphere of any space. The vitreous china material used complies with AS 1776 (Vitreous china used in sanitary appliances).

G1/AS1 2.1: All requirements are satisfied per the Watermark certification to AS 1172.1 (Sanitary plumbing products: Water closet pans) under Licence no. WM–A030020.

G1/AS1 2.2: All requirements are satisfied per the Watermark certification to AS 1172.2 (Sanitary plumbing products: Flushing devices and cistern inlet and outlet valves) under Licence no. WM–A030020.

G12/AS1 3.4.3(a) & 3.5.1: The supplied flush valves have a minimum air gap of 25mm.

Scope of Use

The Nora Back-to-wall Toilets are intended for use for personal sanitation in residential & commercial buildings. All models are floor mounted & are supplied with a Watermark certified S trap pan connector to achieve a wide range of set outs (refer to specification sheet for each model). P trap installation is possible with a straight pan connector. TC-6672B, TC-6672R, TC-6601R, K-800 have top rear or side water inlet options. RN-1001 have side water inlet only.

Conditions of Use

Installation must comply with AS/NZS 3500 and AS/NZS 6400. Englefield Bidet Seats installed to compatible toilets must have High Hazard backflow prevention installed (not supplied). Please refer to the installation instructions for further information.

Must be installed by a registered plumber in accordance with our supplied instructions.

Maximum working pressure: 500kPa. If pressure exceeds 500kPa, a pressure limiting valve must be installed.

Ensure that no part of the cistern inlet hose is submerged in water (top rear water inlet only). The pan must be firmly fixed to the floor using the supplied fixing kit.

This product is cleanable and impervious to moisture — cleaning shall be done in accordance with the supplied cleaning instructions.

Supporting documentation

The following additional documentation supports the above statements:

| Installation instructions | Refer website. |
|---------------------------|----------------|
| Warranty statement | Refer website. |
| Care & maintenance guide | Refer website. |

Warnings and Bans

This product line is not subject to any warning or ban under section 26 of the Building Act 2004.

Contact details

| Manufacture location | China | |
|---|--|--|
| Legal and trading name of manufacturer and importer | Renoarts Ltd | |
| Manufacturer/Importer Address for Service | 25B Lorien Place, East Tāmaki, Auckland 2013 | |
| Manufacturer/Importer Website | www.renoarts.co.nz | |
| Manufacturer/Importer NZBN | 9429041423424 | |
| Manufacturer/Importer Email | info.n@renoarts.co.nz, info.e@renoart.co.nz | |
| Manufacturer/Importer Phone Number | 092716664 | |